

ESD5425E
**4-Lines, Uni-directional, Low Capacitance
Transient Voltage Suppressors**
Descriptions

The ESD5425E is a low capacitance TVS (Transient Voltage Suppressor) array designed to protect high speed data interfaces. It has been specifically designed to protect sensitive electronic components which are connected to data and transmission lines from over-stress caused by ESD (Electrostatic Discharge).

The ESD5425E incorporates four pairs of low capacitance steering diodes plus a TVS diode.

The ESD5425E may be used to provide ESD protection up to $\pm 30\text{kV}$ (contact discharge) according to IEC61000-4-2, and withstand peak pulse current up to 25A (8/20 μs) according to IEC61000-4-5.

The ESD5425E is available in SOT23-6L package. Standard products are Pb-free and Halogen-free.


Features

- Reverse stand-off voltage: 5V max.
- Transient protection for each line according to IEC61000-4-2 (ESD): $\pm 30\text{kV}$ (contact discharge)
IEC61000-4-5 (surge): 25A (8/20 μs)
- Low capacitance: $C_{I/O-GND} = 3\text{pF}$ typ.
- Ultra-low leakage current: $I_R = 20\text{nA}$ typ.
- Low clamping voltage: $V_{CL} = 11.2\text{V}$ @ $I_{PP} = 16\text{A}$ (TLP)
- Solid-state silicon technology


Applications

- USB 2.0
- Video Graphics Cards
- DVI
- IEEE 1394
- Monitors and Flat Panel Displays
- 10/100 Ethernet
- Notebooks


<http://www.sh-willsemi.com>



SOT23-6L



Circuit diagram




5425 = Device code
EA = Special code
YW = Date code

Marking & Pin configuration (Top View)
Order information

Device	Package	Shipping
ESD5425E-6/TR	SOT23-6L	3000/Tape&Reel

Absolute maximum ratings

Parameter	Symbol	Rating	Unit
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	350	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{pp}	25	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	kV
ESD according to IEC61000-4-2 contact discharge		± 30	
Operation junction temperature	T_J	125	$^{\circ}C$
Lead temperature	T_L	260	$^{\circ}C$
Storage temperature	T_{STG}	-55~150	$^{\circ}C$







Electrical characteristics ($T_A = 25^{\circ}C$, unless otherwise noted)

Definitions of electrical characteristics


Electrical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	V_{RWM}				5.0	V
Reverse leakage current	I_R	$V_{RWM} = 5\text{V}$			1	μA
Reverse breakdown voltage	V_{BR}	$I_{BR} = 1\text{mA}$	7.0	8.5	9.5	V
Forward voltage	V_F	$I_F = 10\text{mA}$	0.6	0.9	1.2	V
Clamping voltage ¹⁾	V_{CL}	$I_{PP} = 16\text{A}$, $t_p = 100\text{ns}$		11.2		V
Dynamic resistance ¹⁾	R_{DYN}	$t_p = 100\text{ns}$		0.11		Ω
Clamping voltage ²⁾	V_{CL}	$V_{ESD} = 8\text{kV}$		12		V
Clamping voltage ³⁾	V_{CL}	$I_{PP} = 1\text{A}$, $t_p = 8/20\mu\text{s}$		9.5		V
		$I_{PP} = 25\text{A}$, $t_p = 8/20\mu\text{s}$		14		V
Dynamic resistance ³⁾	R_{DYN}	$t_p = 8/20\mu\text{s}$		0.19		Ω
Junction capacitance	$C_{I/O-GND}$	$V_R = 0\text{V}$, $f = 1\text{MHz}$, $V_{CC} = \text{floated}$, Any I/O to GND		3.0	5	pF
	$C_{I/O-I/O}$	$V_R = 0\text{V}$, $f = 1\text{MHz}$, Any I/O to I/O		1.5	2.5	pF


Notes:

- 1) TLP parameter: $Z_0 = 50\Omega$, $t_p = 100\text{ns}$, $t_r = 2\text{ns}$, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
- 2) Contact discharge mode, according to IEC61000-4-2.
- 3) Non-repetitive current pulse, according to IEC61000-4-5. R_{DYN} is calculated from 5A to 20A.


Typical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)

8/20 μs waveform per IEC61000-4-5

Contact discharge current waveform per IEC61000-4-2

Clamping voltage vs. Peak pulse current

Capacitance vs. Reverses voltage

Non-repetitive peak pulse power vs. Pulse time

Power derating vs. Ambient temperature

Typical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)



ESD clamping
 (+8kV contact discharge per IEC61000-4-2)



ESD clamping
 (-8kV contact discharge per IEC61000-4-2)



TLP Measurement

Package outline dimensions
SOT23-6L


Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	--	--	1.250
A1	0.000	--	0.150
A2	1.000	1.100	1.200
A3	0.600	0.650	0.700
b	0.360	--	0.500
b1	0.360	0.380	0.450
c	0.140	--	0.200
c1	0.140	0.150	0.160
D	2.826	2.926	3.026
E	2.600	2.800	3.000
E1	1.526	1.626	1.726
e	0.900	0.950	1.000
e1	1.800	1.900	2.000
L	0.350	0.450	0.600
L1	0.590REF		
L2	0.250BSC		
R	0.100	--	--
R1	0.100	--	0.200
θ	0°	--	8°
$\theta 1$	3°	5°	7°
$\theta 2$	6°	--	14°